

# AVANT® *e5 e6*

ZERO EMISSION





## ELECTRIC AVANT


### Features:

- No emissions
- Minimal noise level
- Low operating cost
- Battery powered
- Charging unit included in machine
- Standard Avant attachments fit

*e5*



*e6*





# e5 e6

## ZERO EMISSION

Avant e5 and e6 are full electric, battery powered articulated loaders. They can be operated also in indoor and non ventilated spaces which don't allow any exhaust emissions or where there are noise restrictions etc.

Avant e5 is equipped with lead-acid batteries whereas Avant e6 features state-of-the-art lithium-ion technology, which gives as much as three times longer work cycle in hard work.

Charging time of lithium-ion battery is also considerably shorter.

Standard Avant attachments mount on Avant e5 and e6. The auxiliary hydraulic outlet in the front is equipped with the multi connector system with max. 30 l/min flow.



Technical information	AVANT e5	AVANT e6
Length	2470 mm	2550 mm
Width (with standard tires)	1130 mm	1130 mm
Height	1985 mm	1985 mm
Weight, starting from	1520 kg	1400 kg
Standard tires	23x10.50-12" grass/TR	23x10.50-12" grass/TR
Transmission	Hydrostatic	Hydrostatic
Drive speed	10 km/h	10 km/h
Auxiliary hydraulics	30 l/min	30 l/min
Turning radius (inside/outside)	995 / 2050 mm	995 / 2050 mm
Lifting height	2790 mm	2790 mm
Tipping load	900 kg	900 kg
Battery type	Lead-acid	Lithium-ion
Energy	11,5 kW	14,5 kWh
Fuel	Electric	Electric



# AVANT®

**Avant Tecno Oy**

Ylotie 1, 33470 Ylojarvi, FINLAND

Tel. +358 3 347 8800

sales@avanttecno.com

AVANT has a policy of continuing improvement, and retains the right to change specifications without notice. © 2016 AVANT Tecno Oy. All rights reserved.

[www.avanttecno.com](http://www.avanttecno.com)